

Welded Stainless Steel Round Tubes



OD	WALL THICKNESS IN MM																
	1.00	1.20	1.50	1.60	2.00	2.30	2.30	2.60	2.90	3.00	3.05	3.20	3.65	3.91	4.05	4.50	5.00
6.00	0.125																
8.00	0.175																
10.00	0.225		0.319														
12.00	0.275		0.394														
14.00	0.326		0.470		0.601												
15.00	0.351		0.507														
16.00	0.376		0.545		0.701												
17.20				0.625	0.761	0.858											
18.00	0.426		0.625		0.801												
20.00	0.476	0.565	0.695		0.901												
21.30				0.789	0.967												
22.00	0.526	0.625	0.770	1.002													
23.00			0.808														
24.00	0.576																
25.00	0.601	0.715	0.883		1.152		1.409			1.653							
25.40		0.727	0.898														
26.00				1.014	1.247			1.582									
28.00	0.676		0.995		1.302												
30.00	0.726		1.070		1.402		1.722			2.028							
31.80		0.919	1.138										2.498				
32.00			1.146		1.502					2.178		2.444					
33.70				1.286	1.588			2.025									
34.00	0.826		1.221		1.603												
35.00			1.258		1.653												
36.00					1.703					2.479							
38.00			1.371		1.803		2.222			2.629							
38.10		1.109	1.375														
40.00	0.977		1.446		1.903					2.779							
42.40				1.635	2.023			2.591				3.141					
44.50			1.615		2.128			2.728	3.021								
48.30				1.871	2.319			2.975				3.614					
50.00	1.227		1.822		2.404					3.531							
50.50		1.551	1.852														
51.00					2.454												
52.00	1.277		1.897														
53.00		1.934															
54.00					2.604												
57.00			2.085		2.754			3.542	3.929								
60.30				2.352	2.920			3.757	4.168				5.178	5.521			
63.50			2.329														
70.00			2.573		3.405		4.226	4.873									
76.10				2.985	3.711			4.785		5.315			6.535		7.222		
83.00			3.061		4.157												
88.90			3.498		4.352			5.618		6.453			7.795		8.605		10.504
101.60										7.407							
104.00					5.108												
108.00					5.308												
114.30					5.624			7.272		7.632							
129.00					6.360						8.496				11.181	12.372	
133.00					6.560												
139.70					6.896			8.859		9.766							
154.00					7.612					10.269							
159.00					7.863						11.719						
168.30					8.328			10.379			12.417						
204.00					10.116												20.445
254.00					12.620												

Manufactured in accordance with DIN 2463/ASTM A312, weld factor = 1.0. Annealed and pickled or annealed with works certificates according to DIN 50049/31B. 6 metre lengths.

Range of sizes and weight table in Kg/Mtr.

Grades available: W-NI 4301/AISI 304, W-NI 4541/AISI 321, W-NI 4571/AISI 316 TI.